

Black Out Cover

- The cover cuts out all light and is for use in light sensitive areas.
- The Black Out Cover is designed to fit over existing BFM® connectors.
- It is attached using a butterfly mechanism at the top and the base of the cover. This makes installing and removal easy and no tools are required.

✓



VIBRATION

✗



OSCILLATION

✓



COMPRESSION

✗



DUST TIGHT

✓



FOOD SAFETY

✓



FOOD SAFETY

✓



FOOD SAFETY

✗



ATEX

100%

IBEXU

Ex

3

FDA

EC1906/2006

3

FDA

EC1906/2006

3

FDA

EC1906/2006

(*applies to inner Seeflex layer only)



PHYSICAL PROPERTIES:

Fibre	Polypropylene
Colour	Black
Construction/Finish	Multi-filament plain weave, calendered
Weight +/- 10%	207 g/m² 6.1 oz/yd²
Min. Operating Temp	-70°C / -94°F
Max. Operating Temp*	95°C / 203°F
Max. Surge Temp*	100°C / 212°F

*(NB: Limited to max. operating temperature of inner connector)

AVAILABLE SIZES: (in 50mm / 2" increments)

Diameter (also available in 125mm/5")	Ø100mm - 1,650mm (Ø4" - 65")
Length	80mm, 100mm- 1,000mm (3", 4" - 39½")

(Size range is in mm, so inch conversions are approximate only. Restrictions apply for larger diameters. Refer to 'Connector Sizes' for more information)

COMPLIANCE:

Complies with the following regulations:
FDA 21 CFR 177.1520